


The strongest lift on the market

The Savaria HC ceiling lift is designed to easily lift and move heavier patients – up to an industry-leading capacity of 1,200 pounds (544 kg). Designed from the ground up to better serve caregivers and patients, the Savaria HC uses a new-in-its-class motorized lift rotation feature for superior maneuverability even in tight spaces. The uniquely designed motorized 4-point tilting spreader bar provides enhanced patient positioning comfort during transfers. The Savaria HC ceiling lift is fully compatible with standard Savaria low profile track and the sleek motor design means the tight turning radius will be the same as other Savaria fixed lifts. The high efficiency lithium ion battery delivers faster lifting speeds and built-in constant charging means the lift is always ready to use.

When higher capacity lifting is needed, the Savaria HC lift packages together a strong, fast lift that's easy to maneuver. Maintaining a patient's dignity and safety has never been simpler with this thoughtfully designed high capacity ceiling lift.







mmmmmm

THE CHARLES AND A SHARE THE PARTY OF THE PAR

Motorized 360 degree rotation

4-point tilting spreader bar

8-button convenient handset

Key Features:

- Best-in-class weight capacity
- 1,200, 1,000 and 800 lb lift variants
- Motorized track movement and lift rotation
- Motorized 4-point tilting spreader bar
- Compatible with current Savaria track profiles and standard radius curves
- Constant charging system
- · Fastest lift speed
- Superior battery recharge time
- Choose from a full range of bariatric slings
- Integrated scale option available



SAVARIA HC PATIENT LIFT

Safe working load (SWL)	544 kg (1,200 lb), 454 kg (1,000 lb) or 363 kg (800 lb)
Product life expectancy	10 yrs
Lifting speed	5 cm/sec (2 in/sec) at 363 kg (800 lb); 4.5 cm/sec (1.8 in/sec) at 454 kg (1,000 lb);
	4.0 cm/sec (1.6 in/sec) at 544 kg (1,200 lb)
Lifting clearance	56 cm (22 in)
Water ingress protection rating of lift	IP20
Noise level	Maximum 54 dBA
Medical electrical equipment class	Class 1
Protection class	Type BF

CONTROLS

Lift controls	UP and DOWN buttons to raise and lower the lift
Hand control	UP, DOWN, LEFT and RIGHT buttons to raise and lower the lift and move along the track, ROTATE the lift CLOCKWISE or COUNTERCLOCKWISE and tilt the spreader bar in SIT or LAY position
Hand control operating force	4–4.5 N
Water ingress protection rating of hand control	IP67
ON/OFF power switch	Used to shut off power to the lift and as an emergency stop feature

BATTERY & CHARGER

Battery type	Lithium ion, 25.2V 2500 mAh 2 batteries in the device
Battery charging	Full capacity in approximately 4 hours
Constant charging	100-240 VAC, 50-60 Hz
Charger output	29.4 VDC, max 1A

WARRANTY

Parts warranty	3 years

CERTIFICATION: IEC 60601-1:2005 A1:2012 (medical electrical equipment); IEC 60601-1-11:2015 (homecare); ISO 10535:2021 (patient lift); CAN/CSA Z10535.1:15 (patient lift)

COMPLIANCE: CE Marking per MDR (EU) 2017/745 (medical device); 2006/42/EC (machinery directive); 2015/863/EU (ROHS – 100% of components); 2012/19/EU (WEEE)

WARNING: This equipment is not suitable in the presence of flammable anesthetic mixtures with air or oxygen, or with nitrous oxide.

